



## COSH SAFETY DATA SHEET (Control of Substances Hazardous to Health)

### Material identification and use

Chemical Name Industrial grating made of fibreglass reinforced polyester  
Common Name Glass Reinforced Plastic GRP / FRP

Company Identification Fibograte, Fibomarine, Fibotrench, Fibosection, Fibotread  
Application Walkways, trench covers, platforms, structural flooring, stair treads

### Hazard Identification

Acute Effect None by contact, dust produced by cutting or grinding can penetrate the pores of the skin causing itching. Avoid breathing dust.

Routes of entry Skin contact or inhalation of dust whilst cutting  
Medical Note People who have a condition that could be aggravated by dust should avoid cutting or grinding. Use a suitable mask or respiratory system

First aid procedure Operative should be removed from the area and shower with soap and water to remove.  
If eyes are affected flush immediately with sterile eye wash solution

### Chemical data

Appearance Solid flat panels with grid pattern or with additional solid plate bonded. Standard colours are RAL 7047 OR RAL 6010  
Sharp edges or grit applied to top surface. Nil odours. Not soluble in water. Specific gravity 1.6

### Fire fighting measures

Product will eventually burn if in direct contact with fire. All products conform to British Standards for fire tests on building and structural materials and achieve BS476:PART7:1997 Flash point none. Flammability limits nil  
Extinguishing media, water, foam, A,B OR C extinguishers. Black smoke, carbon particles. Use respirator. Self extinguishing

### Waste disposal

Abide by local laws and procedures. Product is not considered a hazardous waste.

### Handling and cutting

Wear masks and goggles when cutting or grinding. Cover all exposed parts of the body. Wear gloves when lifting or moving. If using a jigsaw use Bosch T301CHM otherwise use diamond cutting tools

### Other information

**Please contact GRP GRATING SYSTEMS if you require any further details on installation, chemical resistance and loading properties.**